

### Electrostatic Spray Device

David Edward Wilson

Bryan Michael Kadlubowski

5

Jeffrey Keith Leppla

Wataru Hirose

Yoshihiro Wakiyama

Takeshi Aoyama

Takeshi Mori

10

Toru Sumiyoshi

### Cross-Reference To Related Application

This application is a continuation-in-part of our earlier applications, U.S. Serial No. 09/377,332, filed on Aug 18, 1999 and U.S. Serial No. 09/377,333, filed on Aug 18, 1999.

15

### The Field of Invention

This invention relates to a portable electrostatic spray device designed for personal use.

20

More particularly, this invention relates to a portable electrostatic spray device designed for personal use that provides superior spray quality.

### Background of the Invention

25

Known portable electrostatic spray devices often suffer from poor, inconsistent spray quality when the charge-to-mass ratio of the product varies outside of a predetermined range.

This may occur during transient conditions such as start-up and shut-down, or during steady state conditions such as when environmental conditions vary the load seen by the electrostatic spray device. In start-up conditions, for example, if the electrostatic spray device is allowed to begin spraying before the power supply circuit has fully charged the electrode to a desired potential,

30

then the charge-to-mass ratio of the resulting spray may be below a desired level and may result in a poor quality spray exhibiting larger than desired droplet sizes and uneven spray patterns.

Alternatively, after the electrostatic spray device has been turned off, charge stored in capacitive elements of the device may still be present and result in an after-spray condition until the charge in the capacitive elements has dissipated enough to stop a continuing flow of product from the

35

nozzle of the electrostatic spray device. Further, during operation changes in environmental

conditions such as humidity may significantly change the load seen by the high voltage power supply. Changes in the load will also affect the charge-to-mass ratio of the product and will alter the characteristics of the product spray.

5 United States Patent No. 4,549,243 issued to Owen (the "Owen reference") describes an electrostatic spraying apparatus that can be held in the human hand for applications such as graphic work where it is desired that the area to which the spray is applied can be precisely controlled (Col 1, ll 5-9). A feature of the device disclosed in the Owen reference is that provisions may be made with said device for varying the potential applied to the nozzle, for  
10 example by varying the generator output, e.g. the frequency of production of high voltage pulses and/or their magnitude. The Owen reference discloses that this is advantageous since it enables fine, narrow, sprays to be produced (Col. 6, ll 37-42). Although the Owen reference does recognize a benefit for changing the output of the high voltage generator, the reference does not disclose sensing a spray load and adjusting the output of a high voltage power supply in response  
15 to a changing spray load. Nor does the Owen reference disclose providing user adjustable flow rates or for synchronizing the output of the high voltage power supply with the product flow rate to consistently obtain an optimal charge-to-mass ratio.

United States Patent No. 5,121,884 issued to Noakes (the "Noakes reference") presents an  
20 electrostatic sprayer designed such that potential surface leakage paths along which current may leak from the HT generator are sufficiently long to allow the use of a generator having a smaller than conventional maximum current output (Abstract). The benefit of reducing the current output required from the generator enables it to be built less expensively (Col 1, ll 12-14). Further, the Noakes reference identifies that the majority of the current supplied by the high voltage generator  
25 is surface leakage and unwanted corona discharge, only a portion being current actually used to charge the spray (Col 1, ll 33-37). The solution set forth by Noakes is to limit the surface leakage paths and to account for the leakage current in the current produced by the HT generator. An inherent problem with predicting the losses from the HT generator arises when operating a device in varying atmospheric conditions. With a change in atmospheric conditions (e.g. increased  
30 humidity) losses associated with corona discharge and surface leakage can either increase or decrease. To ensure that a particular device is capable of operation in a variety of atmospheric conditions, the device would need to be designed to function in the worst possible atmospheric condition (i.e. atmospheric condition corresponding with the highest corona discharge or surface leakage current). This would require operating a power supply for the worst case atmospheric  
35 condition thereby generating a significant amount of extra energy in atmospheric conditions that

are not the worst case atmospheric conditions. Operating the power supply in this manner leads to an excess drain on battery power and increasing the possibility of charge build-up within the device leading to increased shock potential.

5     Summary of the Invention

10         The present invention provides an electrostatic spray device that maintains a consistent charge-to-mass ratio in order to maintain a consistent target spray quality. During steady state conditions, the high voltage power supply adjusts the output voltage level in response to changing environmental and/or operating conditions. During transient conditions such as start-up, shut-  
15         down and changing flow rate conditions, the high voltage power supply ensures that the charge-to-mass ratio is maintained. During, start-up, for example, the high voltage power supply charges the high voltage electrode to a predetermined voltage level before the product is delivered to the charging location. During shut-down, the product delivery is stopped before the high voltage power supply shuts off power to the high voltage electrode, and during changes in product flow  
20         rate, the voltage level of the high voltage electrode is adjusted to maintain a consistent charge-to-mass ratio. The present invention also prevents afterspray by discharging the stored charge remaining in storage elements of the high voltage power supply.

20     Brief Description of the Drawings

       Figure 1 is a schematic view of the electrical circuitry of one embodiment of an electrostatic spray device of the present invention;

       Figure 2 is a schematic view of a portion the electrical circuitry of another embodiment of an electrostatic spray device of the present invention;

25         Figure 3 is a schematic view of a portion the electrical circuitry of another embodiment of an electrostatic spray device of the present invention;

       Figure 4 is a schematic view of a portion the electrical circuitry of another embodiment of an electrostatic spray device of the present invention;

30         Figure 5 is a schematic view of a portion the electrical circuitry of another embodiment of an electrostatic spray device of the present invention;

       Figure 6 is a graphical depiction of the operation of another embodiment of the present invention;

       Figure 7 is a graphical depiction of the operation of another embodiment of the present invention.

### Detailed Description of the Preferred Embodiment

A first step in the design of a typical electrostatic spray device starts with identifying the target spray quality for a particular product or application. "Target spray quality" is defined as the combination of one or more of the following: spray droplet diameter, distribution of spray droplet diameter, swath width, and spray diameter. In any particular application, a combination of one, more than one, or all of the above mentioned variables may be needed to define a target spray quality for that application.

To achieve a target spray quality, the output operating variables of the device (e.g. high voltage output, current output, product flow rate) are balanced with a unique set of fluid or product properties (e.g. viscosity, resistivity, surface tension). For a given set of environmental (e.g. temperature, humidity), device operating variables, and fluid properties, a particular charge-to-mass ratio exists for a specific target spray quality. The charge-to-mass ratio is a measure of the amount of electrical charge carried by the atomized spray on a per weight basis and may be expressed in terms of coulombs per kilogram (C/kg). The charge-to-mass ratio provides a useful measure to ensure that the target spray quality is maintained. A change during spraying in any of the fluid properties or device output operating variables will result in a change in the spray quality. This change in spray quality corresponds to a change in the charge-to-mass ratio.

In one aspect of this invention, the electrostatic spray device reacts to changes in environmental and/or operating conditions during steady state operating conditions in order to maintain an optimal charge-to-mass ratio and, thus, maintain an acceptable spray quality. Changes in environmental and/or operating conditions tend to affect the available energy for spray formation due to losses of energy to the atmosphere; typically in the form of increased corona and surface leakage. Generally, in a more humid environment, energy losses that occur at the high voltage electrode increase. For instance, in a high humidity environment such as a bathroom, the energy available at the high voltage electrode is less than would be available in a lower humidity environment because of the increased corona losses and surface leakage. This results in a lower charge-to-mass ratio for a product spray, and may result in an inconsistent spray quality if the device does not react to the environmental and/or operating condition.

Figure 1 shows an electrical schematic of one embodiment of an electrostatic spraying device. The power source 10 shown can be a battery or other power source known in the art. For

example, the power source can be one or more user replaceable battery such as two standard “AAA” batteries. Alternatively, the power source could be user-rechargeable cells, a non-user serviceable rechargeable power pack, or an external source (i.e. “line” supply). In at least one arrangement of the circuitry, power source 10 can be separated from the rest of the circuit by a power switch 20. The power switch 20 can extend the active life of a self-contained power source 10 such as a battery. The power switch 20 can also add a margin of safety to a line-voltage power supply by supplying power to the remainder of the circuit only when the power switch 20 is closed. In one embodiment, the power switch 20 can be a toggle switch that is able to maintain its setting until a later actuation. When switch 20 is turned to the “on” position, power is supplied to the DC/DC Converter 30.

The DC/DC Converter 30 receives an input voltage supply from power source 10, for example, a nominal 3.0 volt supply from two conventional “AAA” type batteries, and converts that to a higher voltage signal such as a 5.0 volt supply. The DC/DC Converter 30 can be, for example, a 3 to 5 V DC converter available from Linear Technology Corporation (Part number LT1317BCMS8-TR). The DC/DC Converter 30 can also be used to send a signal to indicator 40. This signal can be either a portion of the supply signal from power source 10, or a portion of the output signal, for example 5.0 volts. The indicator 40, for example, can be an LED that emits light in the orange range of the visible electromagnetic (EM) spectrum. As shown in Figure 1, the indicator 40 can be arranged to emit visible light only when the power switch 20 is in the “on” position and sufficient voltage is supplied to the indicator 40 from DC/DC Converter 30. A user controlled apply switch 45 can be depressed or turned to the “on” position, depending on the type of switch employed, to complete the power supply circuit and provide power to the voltage regulator 50. The voltage regulator 50 can control the input voltage to a motor 60, if necessary. The nominal voltage output from the voltage regulator can be about 3.3 volts. The voltage regulator 50 can also send an output signal to the high voltage switch 70. The high voltage switch 70, for example, can be a transistor or diode element such as a transistor from NEC Corporation part number 2SA812.

The high voltage switch 70 supplies power to the remaining high voltage generation circuitry in response to a signal from the voltage regulator 50. The high voltage switch 70 sends a signal to both high voltage control block 80 and a signal generator such as square wave generator 90. The high voltage control block 80 compares a signal from storage capacitor 110 and current limiter 170 to an internally set reference voltage. Depending upon the value of the feedback signal from storage capacitor 110 and/or a signal from the current limiter 170, the high voltage

control block 80 will send either an "ON" or an "OFF" signal to the DC/DC converter 100. The high voltage control block 80, for example, can be an op-amp such as Toshiba Corporation part number TC75W57FU.

5           The DC/DC converter 100 converts a lower input voltage to a higher output voltage. For example, the DC/DC converter 100 can convert a nominal input voltage of about 5.0 volts to a higher nominal output voltage of about 25.0 volts. The output from the DC/DC converter 100 charges the storage capacitor 110. The storage capacitor 110 provides an input voltage to the primary coil of the high voltage transformer 120. The frequency of the higher voltage output of  
10   DC/DC converter 100 is controlled, as described in more detail later, by a feedback loop to ensure that a substantially constant supply, such as about a 25.0 volts supply, is available to the high voltage transformer 120 from the storage capacitor 110. The DC/DC converter 100 can be, for example, a DC/DC Converter from Toshiba Corporation such as part number TC75W57FU. The high voltage switch 70 can also send an "ON" signal to the square wave generator 90, which is  
15   also connected to the primary coil of the high voltage transformer 120. This results in about a 25.0 volt peak to peak AC pulses being generated through the primary coil of the high voltage transformer 120. The square wave generator 90 can be, for example, an op-amp element from Toshiba Corporation such as part number TC75W57FU. The turn ratio of the high voltage transformer 120 can be, for example, about 100:1 such that an input voltage of about 25.0 volt at  
20   the primary coil would result in about a 2.5 kV (2500 volt) output voltage from the secondary coil. The output voltage from the high voltage transformer 120 can then be supplied to a voltage multiplier 130.

          The voltage multiplier 130 rectifies the output signal from the high voltage transformer  
25   120 and multiplies it to provide a higher voltage DC output voltage. If the output voltage of the high voltage transformer 120 is about a 2.5 kV AC signal, for example, the voltage multiplier 130 could rectify this signal and multiply it to provide a higher voltage DC output such as a 14.0 kV DC output voltage. In one embodiment, the voltage multiplier 130 can be a six stage Cockcroft-Walton diode charge pump. A stage for a Cockcroft-Walton diode charge pump is commonly  
30   defined as the combination of one capacitor and one diode within the circuit. One skilled in the art would recognize that the number of stages needed with a voltage multiplier is a function of the magnitude of the input AC voltage source and is dependent upon the required output voltage. In one embodiment, the high voltage transformer 120 and the voltage multiplier 130 can be encapsulated in a sealant such as a silicon sealant such as one available from Shin-Etsu Chemical  
35   Company, Ltd. as part number KE1204(A.B)TLV. By encapsulating the high voltage transformer

120 and the voltage multiplier 130 in the sealant, the electrical leakage and corona discharge from these high voltage components can be reduced to increase their efficiency.

A current limiting resistor 140 can be located between the output of high voltage multiplier 130 and the high voltage electrode 150. The current limiting resistor 140 can be used to limit the current output from the high voltage multiplier 130 available to the high voltage electrode 150. In one particular embodiment, the current limiting resistor 140 could be, for example, about 20 megaohms. One skilled in the art would recognize, however, that if a higher output current is desired, then a current limiting resistor with a lower resistance would be desired. Conversely, if a lower output current is desired, then a current limiting resistor with a higher resistance would be desired. The high voltage electrode 150 can be made from a suitable metal or conductive plastic, such as acrylonitrile butadiene styrene (ABS) filled with 10% carbon fibers. A bleeder resistor 160, which is described in more detail below, can also be connected as shown in Figure 1. The current limiter 170 is also connected to the output circuitry of the high voltage multiplier 130.

A ground contact 180 can also be provided to establish a common ground between the circuitry of the electrostatic spraying device and the user in order to reduce the risk of shocking the user. Further, in personal care applications, the ground contact 180 can also prevent charge from building-up on the skin of the user as the charged particles accumulate on the skin of the user. The ground contact 53 can be integrated into apply switch 45 and/or substantially adjacent to apply switch 45 such that the user cannot energize the motor 60 and the high voltage supply circuitry without simultaneously grounding themselves to the device. For example, the apply switch 45 can be made of metal and/or the ground contact can be a conductive contact or a grounding electrode can be located next to apply switch 45.

#### Steady-State Operating Conditions

In the embodiment of the present invention shown in Figure 1, the high voltage control block 80 along with feedback control loop 210 provide a control circuit that reacts to changes in environmental and/or operating conditions. In this embodiment, the high voltage control block 80 is designed with the feedback loop 210 to track and adjust the operation of the high voltage generating circuitry, i.e., the high voltage transformer 120 and the voltage multiplier 130. The feedback loop 210 monitors or tracks the voltage drop in the power supplied to the primary coil of the high voltage transformer 120 such as by monitoring the voltage drop across the storage capacitor 110. The voltage drop across the storage capacitor 110 between switching cycles of the

square wave generator 90 is proportional to the voltage drop at the voltage multiplier 130 and to the voltage drop at the high voltage electrode 150. When the voltage at high voltage electrode 150 drops in response to a spray load, for example, the voltage drop is also seen proportionately in the voltage multiplier 130 and also in the storage capacitor 110 between switching cycles.

5 Thus, the feedback loop 210 can track changes in environmental and/or operating conditions that cause a change in the voltage level at the high voltage electrode 150 by monitoring the voltage level at the storage capacitor 110. The high voltage control block 80 includes a control circuit that compares the signal from the feedback loop 210 to a reference voltage and controls the operation of the DC/DC converter 100 such as through frequency modulation, pulse width  
10 modulation or any other control method known in the art. The control circuit may include, for example, an op-amp circuit using an op-amp such as Toshiba Corporation's part number TC75W57FU. In one embodiment, the high voltage control block 80 may provide a steady signal to the DC/DC converter 100 when the signal from the feedback loop 210 is within a predetermined range. When the DC/DC converter 100 receives the steady signal, the DC/DC  
15 converter 100 may continue to operate at a predetermined frequency. However, when the signal from feedback loop 210 is outside of the predetermined range (e.g., excess losses at the high voltage electrode 150 due to high humidity), the high voltage control block 80 changes the control signal to the DC/DC converter 100, which adjusts the charge frequency of the DC/DC converter 100 in order to bring the voltage level of the storage capacitor 110 back within the predetermined  
20 range. This results in an increased or decreased current supply to the high voltage generating circuitry, i.e. high voltage transformer 120 and the voltage multiplier 130, in order to maintain the desired voltage under varying environmental and/or operating conditions. One skilled in the art would also recognize that feedback loop may monitor the operating conditions of the circuit at other locations such as at the secondary coil of the high voltage transformer 120, within the  
25 voltage multiplier 130, at the current limiting resistor 140, at the high voltage electrode 150, etc.

By varying the current provided to the high voltage generating circuitry depending upon the environmental and/or operating conditions, the present invention reduces the production of excess energy during periods of low spray loading while at the same time providing optimal spray  
30 performance over a wide range of environmental and operating conditions. This allows for more efficient use of stored energy and may increase the usable life of a replaceable battery power source. Further, by reducing the current level during periods of low spray loading, the electrostatic spray device of the present invention can reduce corona leakage, which potentially leads to spark discharges and electrical shocking of the user.



In yet another aspect of the present invention, the device internals may be encased in a moisture-proof barrier in order to improve spray performance during operation in high humidity environments. The barrier prevents atmospheric moisture from penetrating the device and coming in contact with the high voltage components located inside of the device. This reduces corona  
5 discharge and other losses associated with the increased humidity, thereby maintaining the target spray quality. An electrostatic spray device or cartridge, for example, may be sealed around the external portions of the device or cartridge with a barrier layer such as an elastomer such as Surilyn.

#### 10 Transient Conditions

Another aspect of this invention is maintaining the optimal charge-to-mass ratio during transitory conditions, e.g., during start-up, shut-down or varying product flow rates. During start-up, for example, an electrostatic spray device of the present invention can synchronize the charging of the high voltage generating circuitry and the delivery of product to the charging  
15 location. This prevents the product from being sprayed until the product can be charged enough to provide the desired charge-to-mass level of the product so that the device can provide a target spray quality. During shut-down, conversely, the electrostatic spray device can maintain the high voltage electrode at a sufficient potential in order to maintain a consistent charge-to-mass ratio until the product delivery to the charging condition has substantially stopped. This allows the  
20 device to provide a target spray quality until the device is shut down. During periods of varying product flow rates, however, an electrostatic spray device can also synchronize the output of the high voltage generating circuitry with the changing flow rate in order to maintain a consistent charge-to-mass ratio throughout the operation of the device. This allows the device to maintain a target spray quality even if the product flow rate varies.

25

In one aspect of the present invention, such as shown in Figure 6, the high voltage electrode 150 can be energized before power is supplied to the motor 60 that drives the product delivery system. In this embodiment, the product is not delivered to the high voltage electrode 150 until the potential of the electrode is sufficient to provide a consistent charge-to-mass ratio of  
30 the product spray. The elapsed time difference between the time the high voltage generating circuitry is turned on and the time that power is supplied to the motor driving the product delivery system is shown as Delay Time 1. By delaying the operation of the motor 60, the device is able to provide a spray formation at start-up that has the desired charge-to-mass ratio by preventing product delivery to the charging location before the charging location has substantially reached its  
35 target potential.

In another aspect of the invention, the device can continue to provide power to the high voltage electrode 150 until the product delivery to the charging location has been stopped. For example, a second delay, such as the Delay time 2 shown in Figure 6, can be provided at shut-down. In this case, the high voltage generating circuitry is able to maintain the high voltage electrode 150 at the target potential until after the product delivery to the charging location has been stopped. The Delay Time 2 may allow for the electrode 150 to be kept at a sufficient potential to provide a consistent charge-to-mass ratio to charge the last of the product to be supplied such as when the product delivery system has a delay time associated with it or where the product being delivered has some momentum associated with it. In such a system, there may be a delay between when the power supply to the motor 60 is turned off and when the product stops moving towards the charging location. In this case it is desirable to maintain the power to the charging location until the product within the product delivery system has completely stopped. An electronic timer or delay element, for example, may be incorporated into the voltage regulator 50 to provide one or more delays such as Delay Time 1 and Delay Time 2.

Yet another aspect of this invention is shown in Figure 7, which depicts a synchronized power delivery to the high voltage electrode 150 and the motor 60 that corresponds to changing flow rates of the product being delivered to the electrode. By ramping up the high voltage generating circuitry, i.e., the high voltage transformer 120 and the voltage multiplier 130, along with the product delivery rate, an ideal charge-to-mass ratio can be maintained. For example, a flow rate sensor, a motor feedback circuit can be used to provide a feedback signal to the high voltage control block 80 that drives the high voltage generating circuitry. Alternatively, other methods known in the art to monitor or approximate the flow rate of the product can be used within the scope of the present invention. The high voltage control block 80 can then adjust the output of the high voltage generating circuitry so that it is proportional to the product flow rate, maintain the desired charge-to-mass ratio and ensure that the device is delivering a target spray quality.

A further aspect of this invention allows the electrostatic spray device to reduce after-spray. After-spray is defined as when the electrostatic spraying device momentarily continues to spray product after power has been shut down to the high voltage power supply. Electrostatic spray devices with integral high voltage power supplies typically use capacitor-diode ladders to step-up output voltage from a primary high voltage transformer. One suitable capacitor-diode ladder is a Cockcroft-Walton type diode charge pump. Capacitors are also used in electrostatic

spray circuitry to improve the quality in the high voltage output and to reduce variations or noise. After the user turns off the device, the capacitors function as electrical storage elements and store the high voltage charge until the charge is dissipated such as through corona leakage to the atmosphere or a spark discharge to a point having a lower electrical potential (e.g., a shock to a user). This stored charge can continue to provide power to the high voltage electrode 150 and may create enough of a potential difference between the product and nearby surfaces to allow for the product to spray after the power has been cut off to the high voltage power supply until the charge in the capacitors is sufficiently dissipated.

An after-spray condition is undesirable because the device continues to spray product after the user has turned off the device and the spray quality is inconsistent because the charge-to-mass ratio significantly varies. The desired charge-to-mass ratio is not maintained because there is not a consistent supply of high voltage current available to completely atomize the product into a spray. The charge stored within the device can partially atomize the product for a period of time while the charge dissipates to create an after-spray. Since the voltage supply to atomize the product is not constant, the charge-to-mass ratio of the resulting spray will vary resulting in the production of a spray that has varying spray quality. Further, the after-spray condition can produce a spray at an unintended time and/or location, such as continuing to spray after the user has placed the device in a purse or storage cabinet. This can create an unexpected and undesirable mess.

After-spray can be reduced or eliminated by rapidly discharging the capacitive elements after the power has been shut down to the high voltage power supply. In a first embodiment of this invention, a high voltage resistor, such as bleeder resistor 160 shown in Figure 1, can be connected between the high voltage output electrode 150 and a point at a lower potential within the device. The bleeder resistor 160 can provide a path by which excess stored energy in the device, such as the energy stored in the capacitors within the voltage multiplier 130, can be dissipated in a relatively short period of time after the user has completed the spraying operation, thereby reducing the occurrence of after-spray. The bleeder resistor 160 should be selected to have a large enough resistance so that the impedance of bleeder resistor 160 will be significantly high when compared to the output current limiting resistor and the spray load so as to not dramatically effect the quality of spray or output of the high voltage generator during normal operation. If the value of bleeder resistor 160 is too low, bleeder resistor 160 will provide a path of lesser resistance than the resistance represented by the spraying operation. In this case bleeder resistor 160 will drain more current than desired during normal spraying operation. When the

current passing through bleeder resistor 160 in normal spraying operation is too high, there will be insufficient current available for atomizing and charging the product. The bleeder resistor can further shorten the life of a portable power source such as a battery. The bleeder resistor 160 should, however, have a resistance low enough so as to allow for dissipation of stored energy in a relatively short period of time. The time needed to dissipate the stored energy of the device can be estimated by using the value of said capacitance multiplied by the value of bleeder resistor 160 to determine the value of an RC time constant. This relationship is given by:

$$\tau_A = C_D \times R_B$$

Where :

$\tau_A$  = Time to drain approximately 63% of the stored capacitance from spraying device (sec)

$C_D$  = Device capacitance (F)

$R_B$  = Value of bleeder resistor ( $\Omega$ )

This RC time constant,  $\tau_A$ , represents the approximate time required to dissipate approximately 63% of the charge of the storage device. The term  $C_D$  represents a sum of the capacitance from conventional capacitor elements within the high voltage power supply circuit as well as capacitance of the product reservoir and other stray capacitance from within the device.

Therefore, while applying this relationship, which has been adopted from conventional circuitry, it will be understood that in practice,  $\tau_A$  represents a time in which greater than 63% of the stored charge is dissipated.

In some cases, the charge dissipated within  $\tau_A$  is sufficient to reduce the charge within the device to a point where after-spray is reduced or eliminated. However, in some cases, the time  $\tau_A$  may not be sufficient time to drain enough charge to reduce or completely eliminate after-spray. In these cases, the designer may desire to drain the entire stored charge from the within the device. In this case, it will be understood that the following relationship approximates a time,  $\tau_B$ , that will ensure complete dissipation of any stored charge. This relationship is given by:

$$\tau_B = 5 \times \tau_A = 5 \times C_D \times R_B$$

Where :

$\tau_B$  = Time to drain 100% of the stored charge from the spraying device (sec)

$C_D$  = Device capacitance (F)

$R_B$  = Value of bleeder resistor ( $\Omega$ )

One suitable range for a typical bleeder resistor is between about 1 M $\Omega$  and about 100 G $\Omega$ , another suitable range is between about 500 M $\Omega$  and about 50 G $\Omega$ , and yet another suitable range is between about 1 G $\Omega$  and about 20 G $\Omega$ . In one embodiment, for example, it may be desirable to completely drain the stored charge of the power supply in less than about 60 seconds, preferably in less than about 30 seconds, and most preferably in less than about 5 seconds. Using an example to illustrate, if it is desirable to dissipate at least about 63% of the stored charge of an electrostatic spraying device having a capacitance of about 500 pF (the device capacitance can be estimated by the sum of the capacitance in the high voltage power supply, the capacitance within the product reservoir and an estimate of the stray device capacitance) in about 5 seconds or less would require a bleeder resistor having a resistance of no more than about a 10 G $\Omega$  resistor.

$$R_B = 5.0 \text{ sec} / 500 \text{ pF} = 10 \text{ G}\Omega$$

Depending upon the distribution of the capacitance (within voltage multiplier 130, the product reservoir capacitance and other stray capacitance) the 10 G $\Omega$  resistor, although dissipating at least 63% of the stored capacitance, may not in practice always eliminate the after-spray condition. Therefore, to ensure that 100% of the device capacitance is drained in the same 5 second interval the resistance of the bleeder resistor 160 would need to be no more than about 2 G $\Omega$ .

$$R_B = (5.0 \text{ sec} / 500 \text{ pF}) / 5 = 2 \text{ G}\Omega$$

In at least one embodiment, for example, bleeder resistor 160 could be a high voltage resistor having a resistance of about 10 G $\Omega$  such as the high voltage resistor available from Nihon Hydrajinn Company available under the part number LM20S-M 10G.

In another embodiment of this invention shown in Figure 2, a mechanical switch 190 can be provided to reduce the effects of after-spray. The high voltage mechanical switch 190 performs a similar function as bleeder resistor 160 with the exception that the high voltage mechanical switch 190 is not an active circuit element during normal spraying operation. Rather, the mechanical switch is arranged so that during normal spraying operation the switch is in the open position and is not drawing any current. However, when the user intends to cease the spraying operation and de-energizes the device, the high voltage mechanical switch 190 is shifted from the open position to the closed position so that a conductive path exists between the output electrode directly to the grounded side of the device circuit, thereby providing a nearly

instantaneous release for any stored charge within the device. One advantage of the high voltage mechanical switch 190 design is that the conductive path to ground does not need to include a resistor and allows for a faster discharge rate. Further, the conductive path is only available when the device is de-energized, i.e., in the off position, and does not interfere with normal spraying operation by draining energy from the high voltage electrode 150 and will not require the high voltage generating circuitry to generate excess power to compensate for power losses associated with the bleeder resistor 160.

In yet another embodiment shown in Figure 3, the device comprises a high voltage electrical switch 200, such as a transistor, in place of bleeder resistor 160 shown in Figure 1. During normal spraying operation, the switch is in the open position and the conductive path to a point of lower potential of the circuitry is not active. However, upon the operator de-energizing the device, the switch is closed and the conductive path to a point of the circuit having a lower potential is then available to drain the stored charge in the device. Again, the high voltage electrical switch 200 can provide a lower resistance than the bleeder resistor 160 and, thus, allows for a quicker discharge of the stored charge in the device. The high voltage electrical switch 200 further provides a conductive path that is only available when the device is de-energized, i.e., in the off position, and does not interfere with normal spraying operation by draining energy from the high voltage electrode 150 and will not require the high voltage generating circuitry to generate excess power to compensate for power losses associated with the bleeder resistor 160.

One skilled in the art may appreciate that either of the arrangements shown in Figure 2 or Figure 3 may also include a bleeder resistor 160 such as shown in Figure 4. In some cases it may be desirable to control the rate at which the stored capacitance is discharged. In such a case, the bleeder resistor 160 can be connected to either the high voltage mechanical switch 190 or the high voltage electrical switch 200 as shown in Figure 4. Further, one skilled in the art will also recognize that a bleeder resistor and/or mechanical or electrical switches may be arranged in other configurations. For example, Figure 5 shows one alternative configuration in which the bleeder resistor 160 is connected between the voltage multiplier 130 and the current limiting resistor 170 and a point at a lower potential.

In yet another aspect of this invention, a power indicator 40, such as shown in Figure 1, can provide a visual or other indication to signal the user of the device that the device has sufficient life in its batteries to deliver target quality spray. A typical problem with existing electrostatic spraying devices is the poor performance that develops as the voltage level of the

batteries or other power supply decays over extended use. As the available current from the batteries drops, the voltage generated at the high voltage electrode 150 and the speed of the motor 60 decrease at different rates. This can cause a deviation from the target charge-to-mass ratio and can result in a below-target spray quality. An electrostatic spray device of the present invention  
5 can include a circuit that monitors the voltage of the battery, informs the user of the present battery status and shuts down the device when the battery voltage drops below a predetermined level in order to prevent the device from providing a below-target spray quality.

In one embodiment, the power indicator 40 can be an LED, such as an LED that emits a light  
10 in the orange range of the electromagnetic (EM) spectrum when the batteries are within the nominal or target operating voltage range. The signal to the power indicator 40 can be fed from an op-amp within the DC/DC converter 30 that compares the incoming signal from power source 10, e.g., batteries, with a preset reference signal. When the voltage of the power source reaches a predetermined level that corresponds to a predetermined quantity of usable battery life remaining  
15 such as five percent, the DC/DC converter 30 may provide a signal to power indicator 40 that changes the indication status of the indicator, e.g., turn the LED on or off, to indicate that the batteries need replacing. This will allow the user to change the batteries before the voltage level drops to a level that could provide below-target spray quality or that could cause the device to fail to perform during the application process and leave the user with a partially finished application.  
20 Further, the circuit can shut down the device at a predetermined battery voltage to ensure that poor spray performance is not experienced by the user due to depleted batteries. In one embodiment, for example, the circuit can give the user at least enough time to complete one complete product application after the power indicator 40 has indicated that the batteries need to be replaced before shutting down the device.

25

Having shown and described the preferred embodiments of the present invention, further adaptations of the present invention as described herein can be accomplished by appropriate modifications by one of ordinary skill in the art without departing from the scope of the present invention. Several of these potential modifications and alternatives have been mentioned, and  
30 others will be apparent to those skilled in the art. For example, while exemplary embodiments of the present invention have been discussed for illustrative purposes, it should be understood that the elements described will be constantly updated and improved by technological advances. Accordingly, the scope of the present invention should be considered in terms of the following claims and is understood not to be limited to the details of structure, operation or process steps as  
35 shown and described in the specification and drawings.

Incorporation by reference:

Relevant electrostatic spray devices and cartridges are described in the following commonly-assigned, concurrently-filed U.S. Patent Applications, and hereby incorporated by reference:

5

“Electrostatic Spray Device”, which is assigned Attorney Docket No. 8395.

“Electrostatic Spray Device”, which is assigned Attorney Docket No. 8396.

“Disposable Cartridge For Electrostatic Spray Device”, which is assigned Attorney Docket No. 8397.

10

WHAT IS CLAIMED IS:

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000